Flute Filler

Molded Polystyrene Insulation.

ThermaFoam R-Control molded polystyrene insulation is a costeffective, durable, and energy efficient solution for insulation applications. ThermaFoam R-Control Flute Filler acts as the void filler and is designed to be installed over existing metal roofs. It provides a uniform and level substrate and is installed prior to the new roof system.

- · Cost effective roof insulation
- R-value that never changes and is stable over time
- Range of compressive strength available
- · Closed cell insulation with superior moisture resistance
- Improve R-value of roof assembly

Strength/R-value.

THERMA FOAM R-CONTROL	Compressive Strength ¹ , psi	R-value/inch ²	
		75°F³	40°F⁴
100	10	3.9	4.2
130	13	3.9	4.3
150	15	4.2	4.6
250	25	4.4	4.8

- Compressive strength @ 10% deformation.
- ² R-value units are °F·ft²·h/Btu.
- ³ Recommended for design in WARM climates. ⁴ Recommended for design in COLD climates.

ThermaFoam R-Control is available in a wide range of R-values and thicknesses to meet your needs. Product thicknesses are provided in the ThermaFoam R-Control Thickness Selector. Project requirements vary, so ThermaFoam R-Control can be ordered in any R-value thicknesses to meet your needs.

Proven to meet, or exceed, building codes.

ThermaFoam R-Control is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER40338-01. ThermaFoam R-Control meets ASTM C578, "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation".




Sizes and Shapes.

ThermaFoam R-Control Flute Filler can be custom cut to match the profile of the metal flutes on your building. Flute Filler strips are easy to install and provide the necessary support under the roofing membrane. Custom cut and square cut ThermaFoam R-Control Flute Filler is available to meet the size requirements of any size flute.

Custom cut ThermaFoam R-Control Flute Filler will fill the entire flute space, improving energy efficiency. Square cut ThermaFoam R-Control Flute Filler insulation is an economical way to fill voids in profile roof decks and still provide additional insulation value to each project.





FOAM FACTS:

ThermaFoam R-Control outperforms XPS.

- ThermaFoam R-Control provides a stable long-term R-value at a lower cost
- ThermaFoam R-Control uses a blowing agent with 10×10 lower global warming potential and $10,000 \times 10^{-2}$ lower ozone depletion
- · ThermaFoam R-Control meets strength requirements at a lower cost
- ThermaFoam R-Control and XPS have resistance to moisture, but ThermaFoam R-Control has a higher vapor permeance leading to superior drying potential

Performance Value.

When you consider all performance characteristics and cost, ThermaFoam R-Control is your best choice for foam insulation.

ThermaFoam R-Control has air in its closed cells and therefore has a stable R-value. Many other insulations use blowing agents that cause R-value loss and are harmful to the environment.

ThermaFoam R-Control has compressive strength to meet specific project requirements.

ThermaFoam R-Control is manufactured to resist moisture absorption in wetting conditions and release absorbed moisture quickly during drying periods, which means ThermaFoam R-Control maintains R-value.

Termite Resistant.

One of the most destructive forces anywhere is termites. ThermaFoam R-Control can be manufactured with borate, a proven and safe additive, that effectively resists termites.

ThermaFoam R-Control with borate meets ICC ES AC239, "Acceptance Criteria for Termite-Resistant Foam Plastics".

Recyclable.

After it's life as a building insulation, ThermaFoam R-Control is 100% recyclable. It can be ground into granules and reincorporated into new ThermaFoam R-Control products or it can be thermally processed into a resin that's used to manufacture other new products.

Ready to take control? Start here.

If you're ready to have ThermaFoam R-Control contribute to your next project, just contact your ThermaFoam R-Control Technical Sales Representative. They will be happy to give you design consultation, information about ThermaFoam R-Control products, pricing, and answers to all of your questions.

Office: 501-945-1114



sales@thermafoamrcontrol.com | www.thermafoamrcontrol.com



203 South Redmond Road Jacksonville, AR 72076